



Nitrile

## Offers tactility and comfortable protection across numerous applications

- Made of a soft nitrile formulation for comfortable fit and feel
- Lightweight construction for tactile sensitivity and fine motor control
- Designed for a broad range of applications across all industries
- Textured on the fingertips for secure handling of tools and materials



### Industries

- Dental
- Food Processing
- Government
- Healthcare
- Janitorial / Sanitation
- Automotive
- Life Sciences
- Manufacturing

### Recommended For

- General dentistry
- Animal health
- Food processing and handling
- Standard patient examinations
- Laboratory analysis
- Catering/Meal preparation
- Light assembly tasks
- Light duty maintenance
- Multipurpose use: Dish Washing, Cleaning, Pet Care & Grooming, Food Preparation, Gardening & many more!



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

	<b>92-134</b>
<b>Material</b>	Nitrile
<b>Color</b>	Blue
<b>Glove Design</b>	Chlorinated, Powder-Free, Textured Fingers
<b>Cuff</b>	Beaded
<b>Manufacturing/QMS Audit Standards</b>	ISO 13485, ISO 9001
<b>#PDS.DisposableGlove.Regulatory#</b>	ASTM D6319, CE 0493, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 455 1-4, FDA21 CFR 177-2600, Food Contact, ISO 13485, ISO 9001, US QSR/FDA 510(k) Medical Examination Grade
<b>Packaging</b>	100 gloves per dispenser, 10 dispensers per case, 1000 gloves per case
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	China, Malaysia
<b>User Needs Segment</b>	High Touch
<b>Available sizes</b>	XS (5.5 - 6), S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
<b>Anti-static</b>	No

### PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D6319
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151
Palm Thickness (mm/mils)	0.07 / 2.8		ASTM D6319
Finger Thickness (mm/mils)	0.11 / 4.3		ASTM D6319
	<b>BEFORE AGING</b>	<b>AFTER AGING</b>	
Ultimate Tensile Strength (MPa)	14	14	ASTM D412 & D573
Elongation at Break (%)	500	400	ASTM D412 & D573
Force at break (N)	6	6	EN 455-2

### ORDERING INFORMATION

Size	XS (5.5 - 6)	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
<b>Product Code</b>	92134060	92134070	92134080	92134090	92134100

### Performance Standards and Regulatory Compliance

