

# A+ Aloe<sup>®</sup> N88 Robust Aloe & Chamomile Coated Nitrile Glove



## Offers comfortable, reliable protection for tough jobs with aloe & chamomile

- Designed with Ansell's proprietary aloe and chamomile inner coating
- Manufactured with a robust profile for added durability & chemical splash resistance



#### **Industries**

- Life Sciences
- Machinery and Equipment
- Manufacturing
- Healthcare

#### **Recommended For**

- Assembly of parts
- Light chemical handling
- Maintenance
- Sample taking and processing
- Laboratory analysis
- Standard patient examinations







### A+ Aloe® N88

**Robust Aloe & Chamomile Coated Nitrile Glove** 

#### **TECHNICAL DATA SHEET**

#### **PRODUCT INFORMATION**

|                           | A+ Aloe <sup>®</sup> N88   |
|---------------------------|--|
| Material                  | Nitrile  |
| Color                     | Green  |
| Glove Design              | Aloe & Chamomile Coating, Textured Fingers   |
| Cuff                      | Beaded   |
| Regulatory                | ASTM D6319, FDA21 CFR 177-2600-US Food Contact Approved, US QSR/FDA 510(k) Medical Examination Grade     |
| Packaging                 | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case                                     |
| Storage                   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country of Origin         | Indonesia  |
| <b>User Needs Segment</b> | Robust   |
| Available sizes           | S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10), XXL (10.5 - 11)                                    |
| Anti-static               | Not Tested   |

#### **PHYSICAL PROPERTIES**

|   | Typical Values      |             | Testing Method      |
|---|---------------------|-------------|---------------------|
| Length (mm/inches)                      | 250 / 9.8           |             | ASTM D3767,EN 420   |
| Freedom from Holes (Inspection level I) | 1.5 AQL             |             | ASTM D5151,EN 455-1 |
| Palm Thickness (mm/mils)                | 0.12 / 4.7          |             | ASTM D3767,EN 420   |
| Finger Thickness (mm/mils)              | 0.15 / 5.9          |             | ASTM D3767,EN 420   |
|   | <b>BEFORE AGING</b> | AFTER AGING |                     |
| Ultimate Tensile Strength (MPa)         | ≥16                 | ≥ 14        | ASTM D412 & D573    |
| Elongation at Break (%)                 | ≥ 500               | ≥ 400       | ASTM D412           |
| Force at break (N)                      | ≥6                  | ≥6          |                     |

#### ORDERING INFORMATION

| Size         | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|-------------|-------------|-------------|---------------|
| Product Code | N881-10     | N882-10     | N883-10     | N884-10       |

#### For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region North America Region

Ansell Healthcare Europe NV T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center (Malaysia) Sdn Bhd T: +603 8310 6688 F: +603 8310 6699

Ansell Healthcare Products LLC T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited T: +61 1800 337 041 F: +61 1800 803 578

Russia

Ansell PYC Ten. +7 495 258 13 16

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.



Ansell